

Ingredients:

Chemical Name	CAS Number:	Proportion:
Bitumen (65996-93-2)		<60%
Liquid Hydrocarbons (8042-47-5)		<60%

HEALTH HAZARD INFORMATION

Health Effects:

Acute

Swallowed:	Give a glass of water. Do not induce vomiting. Seek medical advice.
Eyes:	Flush thoroughly with water for a least 15 minutes. If irritation persists, seek medial attention.
Skin:	Remove contaminated clothing. Wash skin thoroughly with soap and water.
Inhaled:	Remove the affected person to fresh air.

Chronic

Threshold limit value [TLV] for liquid Hydrocarbons - 100ppm. Contact with liquid or vapours may cause irritation to skin, eyes, nose and throat. Inhalation of the vapour may cause headaches and dizziness.

First Aid

Advice	For advise, contact a Poisons Information Centre (Phone eg. Australia 13 11 26; New Zealand 03 4747 000 [Not after May 2005] or 0800 764 766 or a doctor at once).
Swallowed	If swallowed, do NOT induce vomiting.
Eyes	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
Skin	If skin contact occurs, immediately remove contaminated clothing. Flush skin under water for 15 minutes. They apply calcium gluconate gel. Contact the Poisons Information Centre.

Safety Points

Wear eye protection when mixing or using.
Wear protective gloves when mixing or using
Do not mix with hot water

Advice to Doctor:

Treat Symptomatically

PRECAUTIONS FOR USE

Exposure Standards:	TLV Liquid Hydrocarbons - 100ppm
Engineering Controls:	Local exhaust or well ventilated area. In poorly ventilated areas a respirator suitable for organic vapours should be worn.
Personal Protection:	PVC gloves and safety gloves.
Flammability:	Avoid strong oxidising agents and do not use to sources of ignition.

SAFE HANDLING INFORMATION

Storage and Transport:	Follow guidelines for Australian Standard AS1940 and the appropriate Dangerous Goods Regulations.
Spills and Disposal:	Where possible excess material should be transferred to a sound container for small spills or the residue should be absorbed onto a suitable absorbent such as earth, sand or saw dust. Do not allow the product to enter drains or water ways.
Fire / Explosion Hazard:	The product is flammable. A fire may be fought with Dry chemical, foam, carbon dioxide. Exposed containers should be cooled with water spray.

OTHER INFORMATION

None Available

CONTACT POINT

ORGANISATION	TELEPHONE	ASK FOR
Poisons Information Centre – Australia Wide	131126	
Eazygleam Products Pty Ltd	+61-(0)7-3274 2593	Andrew Gilbert
Fire Brigade	000	Fire Brigade
Police	000	Police

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. Customers are encouraged to conduct their own tests as end user suitability of the product for particular uses is beyond our control. The information is not intended as an inducement to bargain and no warranty expressed or implied is made as to its accuracy, reliability or completeness. Eazygleam Pty Ltd accepts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet except in conjunction with the proper use of the product to which it refers. Due care should be taken that the use and disposal of this product is in compliance with appropriate Federal, State and Local Government regulations.